

TC57 — Ficha técnica

Resumen de especificaciones extraído de la ficha oficial en línea: TC52 and TC57 Series Touch Computer Specification Sheet | Zebra | Zebra

Fuente oficial: <https://www.zebra.com/us/en/products/spec-sheets/mobile-computers/handheld/tc52-tc57.html>

Consulta y generación: 2026-08-05. Las especificaciones pueden variar por configuración y región.

Physical Characteristics

Dimensions	6.1 in. L x 2.9 in. W x 0.73 in. H 155 mm L x 75.5 mm W x 18.6 mm H
Weight	8.8 oz./249 g with battery
Display	5.0 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel
Imager Window	Corning Gorilla Glass
Touchpanel	Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti-smudge coating
Backlight	LED backlight
Power	Rechargeable Li-Ion, PowerPrecision+, > 15.48 Watt hours, > 4150 mAh, improved battery metrics for better battery management, fast charging (up to 2.4 A)
Expansion Slot	User accessible microSD up to 32GB SDHC and up to 256 GB SDXC
SIM Slots	TC57 only: 1 nano SIM; 1 eSIM
Network Connections	TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN
Notification	Audible tone; multi-color LEDs; vibration
Keypad	On-screen keypad and enterprise keyboard
Voice and Audio	Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio
Buttons	Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons

Performance Characteristics

CPU	Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz
Operating System	TC52: Upgradeable to Android 14 TC57: Upgradeable to Android 14
Memory	4GB RAM/32GB Flash

User Environment

Operating Temp.	-4°F to 122°F/-20°C to 50°C
Storage Temp.	-40°F to 158°F/-40°C to 70°C
Humidity	5% to 95% non-condensing
Drop Specifications	Multiple 6 ft. drops to concrete with the rugged boot accessory per Mil STD 810 G; Multiple 4 ft/1.2m drops to tile over concrete -10°C to 50°C (14°F to 122°F)
Tumble Specification	500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification
Sealing	IP68 and IP65 per applicable IEC sealing specifications
Vibration	4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random (20 Hz to 2 kHz); 60 minute duration per axis, 3 axis
Thermal Shock	-40° F to 158° F/-40° C to 70° C rapid transition

Electrostatic Discharge (ESD)	+/- 15kv air discharge; +/- 8kv direct discharge; +/- 8kv indirect discharge
--------------------------------------	--

Interactive Sensor Technology (IST)

Light Sensor	Automatically adjusts display backlight brightness
Magnetometer	eCompass automatically detects direction and orientation
Motion Sensor	3-axis Accelerometer with MEMS Gyro
Pressure Sensor	Automatically detects altitude information for locating (TC57 only)
Proximity Sensor	Automatically detects when the user places the handset against head during a phone call to disable display output and touch input

Data Capture

Scanning	SE4710 imager (1D and 2D) with extraordinary range: Scan range – Code 39 barcode: 20 Mil: 2.0 in. to 30.0 in./5.08 cm to 76.2 cm 4 Mil: 3.3 in. to 8.8 in./8.4 cm to 22.4 cm Digimarc support
Camera	Front — 5 MP; f/2.0 aperture Rear — 13 MP autofocus; f/2.2 aperture; flash LED generates balanced white light; supports Torch mode
NFC	ISO 14443 Type A and B; FeliCa and ISO 15693 cards; P2P mode and Card Emulation via Host. TC57 Only: Card Emulation via Host and UICC

Wireless WAN Data and Voice Communications (TC57 Only)

Radio Frequency Band	Supports VoLTE , Carrier Aggregation up to 3DL CA AT&T; FirstNet Ready certification Verizon PNTM certification LTE FDD: 700/800/850/900/1800/1900/AWS/2100/2600 (28,13,14,12,17/19,20/5,26/8/3/2,25/4,66/1/7); LTE TDD: 1900/2300/2500 (39/40/41,38); UMTS/HSPA/HSPA+: 850/900/AWS/1900/2100 (5/8/4/2/1); GSM/GPRS/EDGE: 850/900/1800/1900
GPS	TC57 only: Autonomous, Concurrent GPS; GLONASS; Gallileo; BeiDou, and A-GPS. Supports IZAT™ XTRA
Multimedia	Wi-Fi Multimedia™ (WMM) and WMM-PS; Including TSPEC

Wireless LAN

Radio	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v3/w; Wi-Fi™ certified; IPv4, IPv6, 2x2 MU-MIMO TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v3/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz 2x2 MU-MIMO
Data Rates	5GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4GHz: 802.11b/g/n — up to 300 Mbps
Operating Channels	Channel 1-13 (2412-2472 MHz): 1,2,3,4,5,6,7,8,9,10,11, 12,13 Channel 36-165 (5180-5825 MHz): 36,40,44,48,52 56,60,64,100,104,108,112,116,120,124,128,132,136,140, 144,149,153,157,161,165 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency.
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC and LEAP.EAP-PWD
Certifications	WFA (802.11n, WMM-PS, 801.11ac, PMF)
Fast Roam	PMKID caching; Cisco CCKM; 802.11r; OKC

Wireless PAN

Bluetooth	Class 2, Bluetooth v5.0, Bluetooth Low Energy (BLE)
------------------	---