

Ficha técnica

Epson

Modelos / familias

ACULASER-M4000

Fuente del fabricante

User's Guide (v1.0)

<https://download.epson-europe.com/pub/download/3206/epson320624eu.pdf>

Las páginas siguientes son un extracto técnico del documento oficial del fabricante.

Printer language:	ECP/Page printer language
	ESC/P 2 24-pin printer emulation (ESC/P 2 mode)
	ESC/P 9-pin printer emulation (FX mode)
	IBM Proprinter emulation (l239X mode)
	Adobe PostScript3 (PS3 mode) PCL6/PCL5 emulation (PCL mode)
Resident fonts:	84 scalable fonts, and 7 bitmap fonts for ESC/Page 95 scalable fonts, and 5 bitmap for PCL5 80 scalable fonts, and 1 bitmap for PCL6 17 scalable fonts for PostScript3
RAM:	64 MB, expandable up to 576 MB

* Printing speed varies by paper source or other conditions.

Environmental

Temperature:	In use:	10 to 32°C (50 to 90°F)
	Not in use:	-20 to 40°C (-40 to 104°F)
Humidity:	In use:	15 to 85% RH
	Not in use:	5 to 85% RH
Altitude:	3,500 meters (11,483 feet) maximum	

Mechanical

Dimensions	Height:	404 mm (15.9 in.)
	Width:	428 mm (16.9 in.)
	Depth:	480 mm (18.9 in.)
Weight	Approx. 21.5 kg (about 47.4 lb) (Excluding consumables and options)	

Electrical

			120 V Model L541A	220-240 V Model L541A
Rated voltage			110 V-120 V	220 V-240 V
Rated frequency			50 Hz / 60 Hz	50 Hz / 60 Hz
Rated current			11 A	5.5 A
Power consumption	During printing	Average	662 W	654 W
		MAX	1090 W	1120 W
	During ready mode		78 W	77 W
	During sleep mode*		Up to 7 W	Up to 10 W

* Values represent power consumption while all operations are completely suspended. Power consumption varies depending on errors and operating conditions, and whether a type B interface card is installed or a USB memory is inserted.

Standard and approvals

European model:

Low Voltage Directive 2006/95/EC EN 60950-1
 EMC Directive 2004/108/EC EN 55022 Class B
 EN 55024
 EN 61000-3-2
 EN 61000-3-3

Interfaces

Parallel Interface

Use the IEEE 1284-I compliant parallel interface connector.

ECP mode/Nibble mode

USB interface

USB 2.0 High Speed mode

Note:

- ❑ *Only computers equipped with a USB connector and running Windows XP, XP x64, Me, 98, 2000, Server 2003, or Server 2003 x64, support the USB interface.*
- ❑ *Your computer must support USB 2.0 in order to use USB 2.0 as the interface to connect your computer to the printer.*
- ❑ *Since USB 2.0 is fully compatible with USB 1.1, USB 1.1 can be used as an interface.*
- ❑ *USB 2.0 can be used with Windows XP, XP x64, 2000, Server 2003, and Server 2003 x64, operating systems. If your operating system is Windows Me or 98, use a USB 1.1 interface.*

Ethernet interface

You can use an IEEE 802.3 100BASE-TX/10 BASE-T straight-through shielded, twisted-pair interface cable with an RJ45 connector.

Options and Consumable Products

Optional paper cassette unit

Product code:	C12C802471
Paper size:	A4, A5, B5, Letter (LT), Half-Letter (HLT), Executive (EXE), Legal (LGL), Government Letter (GLT), Government Legal (GLG), F4
Paper weight:	64 to 216 g/m ² (17 to 57.4 lb)
Paper feed:	One paper cassette mounted Automatic feed delivery system Cassette capacity up to 550 sheets (When using 80 g/m ² paper)
Paper types:	Plain paper, Thick paper, labels, envelopes, transparencies
Power supply:	DC 24V / 1.0 A and DC 3.3 V / 0.2 A supplied by the printer
Model:	JEA-7*
Dimensions and weight:	
Height:	143 mm (5.6 in.)
Width:	422 mm (16.6 in.)
Depth:	452 to 510 mm (17.8 to 20.1 in.)
Weight:	6.3 kg (13.9 lb) including cassette

* This product conforms to CE marking requirements in accordance with EC Directive 2004/108/EC.

Duplex Unit

Product code:	C12C802481
Paper size:	A4, A5, B5, Letter (LT), Half-Letter (HLT), Executive (EXE), Legal (LGL), Government Letter (GLT), Government Legal (GLG), F4
Paper weight:	64 to 216 g/m ² (17 to 57.4 lb)
Paper feed:	Automatic feed delivery system
Paper types:	Plain paper, Thick paper
Power supply:	DC 24V / 1.0 A and DC 3.3 V / 0.2 A supplied by the printer
Model:	JEA-8*
Dimensions and weight:	
Height:	238 mm (9.4 in.)
Width:	352 mm (13.8 in.)
Depth:	146 mm (5.8 in.)
Weight:	1.9 kg (4.2) including cassette

* This product conforms to CE marking requirements in accordance with EC Directive 2004/108/EC.

Stacker

Product code:	C12C802111
Output capacity:	Up to 500 sheets (When using 80 g/m ² paper)
Paper size:	Regular or custom paper sizes within the following size: Width: 89.90 - 215.90 mm Length: 139.70 - 355.60 mm However, when using custom size paper that is 76.2 mm to 89.9 mm wide and 127.0 mm to 139.7 mm long, the paper cannot be output to the Stacker so it is output to the face-down tray.
Paper types:	Plain paper, Thick paper, labels, envelopes, transparencies
Power supply:	DC 24V - 0.4A supplied by the printer
Power consumption:	3.3V - 0.2A
Model:	JEA-5*
Dimensions and weight:	
Height:	227 mm (8.9 in.)
Width:	418 mm (16.5 in.)
Depth:	313 mm (12.3 in.)
Weight:	2.6 kg (5.7 lb)

* This product conforms to CE marking requirements in accordance with EMC Directive 2004/108/EC.

Memory modules

Make sure that DIMM you purchase is compatible with EPSON products. For details, contact the store where you purchased this printer or the EPSON sales company.

Memory size:	64 MB, 128 MB, or 256 MB
--------------	--------------------------

Hard Disk Drive

Product code:	C12C824172
Capacity:	37.2 GB